




Investigation of kicker duration and kicker strength




Holger Schlarb, Frank Obier
DESY
22607 Hamburg

Results of measurements





Kicker setup in the Tunnel



Results of measurements



5. Kicker setup in the Tunnel




4/14/2007

Holger Schlarb, DESY

Courtesy: Frank Obier

Results of measurements



Ferrites




4/14/2007

Holger Schlarb, DESY

Courtesy: Frank Obier

Results of measurements

$C = 39\text{nF}$ (1000ns) 12 nF (500ns) 4nF (290ns) 3nF (200ns)



2007-01-09T113426-scan-kicker-delay-new

beam energy = 683.0 MeV
 kicker HV = 3.54 kV
 kick strength = 0.720 mrad
 integrated B^*dl = 1.640 mTm
 kick strength/HV = 0.203 mrad/kV
integrated $B^*dl/HV = 0.463\text{ mTm/kV}$

2007-01-23T182032-scan-kicker-delay-new

beam energy = 480.0 MeV
 kicker HV = 3.00 kV
 kick strength = 0.367 mrad
 integrated B^*dl = 0.587 mTm
 kick strength/HV = 0.122 mrad/kV
integrated $B^*dl/HV = 0.196\text{ mTm/kV}$

⇒ The kicker strength is reduced by about a factor of 2.3

⇒ If 28kV can be applied 0.197mTm/kV provides 3.3mrad kick @500MeV (fulfill specs)