Chapter 4

Object-Oriented Concepts

Peter Müller
Globewide Network Academy (GNA)
pmueller@uu-gna.mit.edu

The previous sections already introduce some "object-oriented" concepts. However, they were applied in an procedural environment or in a verbal manner. In this section we investigate these concepts in more detail and give them names as used in existing object-oriented programming languages.

4.1 Implementation of Abstract Data Types

The last section introduces abstract data types (ADTs) as an abstract view to define properties of a set of entities. Object-oriented programming languages must allow to *implement* these types. Consequently, once an ADT is implemented we have a particular representation of it available.

Consider again the ADT *Integer*. Programming languages such as Pascal, C, Modula-2 and others already offer an implementation for it. Sometimes it is called *int* or *integer*. Once you've created a variable of this type you can use its provided operations. For example, you can add two integers:

```
int i, j, k;     /* Define three integers */

i = 1;           /* Assign 1 to integer i */
j = 2;           /* Assign 2 to integer j */
k = i + j;       /* Assign the sum of i and j to k */
```

Let's play with the above code fragment and outline the relationship to the ADT *Integer*. The first line defines three instances i, j and k of type *Integer*. Consequently, for each instance the special operation *constructor* should be called. In our example, this is internally done by the compiler. The compiler reserves memory to hold the value of an integer and "binds" the corresponding name to it. If you refer to i you actually refer to this memory area which was "constructed" by the definition of i. Optionally, compilers might choose to initialize the memory, for example, they might set it to 0 (zero).

The next line

```
i = 1;
```

sets the value of i to be 1. Therefore we can describe this line with help of the ADT notation as follows:

Perform operation set *with argument* 1 *on the Integer instance* i. *This is written as follows:* i.set(1).

We now have a representation at two levels. The first level is the ADT level where we express everything that is done to an instance of this ADT by the invocation of defined operations. At this level, pre- and postconditions are used to describe what actually happens. In the following example, these conditions are enclosed in curly brackets.

{ Precondition: $i = n$ where $n \in$ Integer }
i.set(1)
{ Postcondition: $i = 1$ }

Don't forget that we currently talk about the ADT level! Consequently, the conditions are mathematical conditions.

The second level is the implementation level, where an actual *representation* is chosen for the operation. In C the equal sign "=" implements the *set()* operation. However, in Pascal the following representation was chosen:

```
i := 1;
```

In either case, the ADT operation *set* is implemented.

Let's stress these levels a little bit further and have a look at the line

```
k = i + j;
```

Obviously, "+" was chosen to implement the *add* operation. We could read the part "i + j" as "add the value of j to the value of i", thus at the ADT level this results in

{ Precondition: Let $i = n_1$ and $j = n_2$ with $n_1, n_2 \in$ Integer }
i.add(j)
{ Postcondition: $i = n_1$ and $j = n_2$ }

The postcondition ensures that i and j do not change their values. Please recall the specification of *add*. It says that **a new** Integer is created the value of which is the sum. Consequently, we must provide a mechanism to access this new instance. We do this with the *set* operation applied on instance k:

{ Precondition: Let $k = n$ where $n \in$ Integer }
k.set(i.add(j))
{ Postcondition: $k = i + j$ }

As you can see, some programming languages choose a representation which almost equals the mathematical formulation used in the pre- and postconditions. This makes it sometimes difficult to not mix up both levels.

4.2 Class

A *class* is an actual *representation* of an ADT. It therefore provides implementation details for the data structure used and operations. We play with the ADT *Integer* and design our own class for it:

```
class Integer {
attributes:
  int i

methods:
  setValue(int n)
  Integer addValue(Integer j)
}
```

In the example above as well as in examples which follow we use a notation which is not programming language specific. In this notation `class {...}` denotes the definition of a class. Enclosed in the curly brackets are two sections `attributes:` and `methods:` which define the implementation of the data structure and operations of the corresponding ADT. Again we distinguish the two levels with different terms: At the implementation level we speak of "attributes" which are elements of the data structure at the ADT level. The same applies to "methods" which are the implementation of the ADT operations.

In our example, the data structure consists of only one element: a signed sequence of digits. The corresponding attribute is an ordinary integer of a programming language[1]. We only define two methods *setValue()* and *addValue()* representing the two operations *set* and *add*.

Definition 4.2.1 (Class) *A* **class** *is the implementation of an abstract data type (ADT). It defines* **attributes** *and* **methods** *which implement the data structure and operations of the ADT, respectively.*

Instances of classes are called *objects*. Consequently, classes define properties and behaviour of sets of objects.

4.3 Object

Recall the employee example of chapter 3. We have talked of *instances of abstract employees*. These instances are actual "examples" of an abstract employee, hence, they contain actual values to represent a particular employee. We call these instances *objects*.

Objects are uniquely identifiable by a *name*. Therefore you could have two distinguishable objects with the same set of values. This is similar to "traditional" programming languages where you could have, say two integers i and j both of which equal to "2". Please notice the use of "i" and "j" in the last sentence to name the two integers. We refer to the set of values at a particular time as the *state* of the object.

Definition 4.3.1 (Object) *An* **object** *is an instance of a class. It can be uniquely identified by its* **name** *and it defines a* **state** *which is represented by the values of its attributes at a particular time.*

The state of the object changes according to the methods which are applied to it. We refer to these possible sequence of state changes as the *behaviour* of the object:

Definition 4.3.2 (Behaviour) *The* **behaviour** *of an object is defined by the set of methods which can be applied on it.*

[1] You might ask, why we should declare an Integer class if there is already an integer type available. We come back to this when we talk about *inheritance*.

We now have two main concepts of object-orientation introduced, class and object. Object-oriented programming is therefore the implementation of abstract data types or, in more simple words, the writing of classes. At runtime instances of these classes, the objects, achieve the goal of the program by changing their states. Consequently, you can think of your running program as a collection of objects. The question arises of how these objects *interact*? We therefore introduce the concept of a *message* in the next section.

4.4 Message

A running program is a pool of objects where objects are created, destroyed and *interacting*. This interacting is based on *messages* which are sent from one object to another asking the recipient to apply a method on itself. To give you an understanding of this communication, let's come back to the class *Integer* presented in section 4.2. In our pseudo programming language we could create new objects and invoke methods on them. For example, we could use

```
Integer i;      /* Define a new integer object */
i.setValue(1); /* Set its value to 1 */
```

to express the fact, that the integer object i should set its value to 1. This is the message "Apply method *setValue* with argument 1 on yourself." sent to object i. We notate the sending of a message with ".". This notation is also used in C++; other object-oriented languages might use other notations, for example "->".

Sending a message asking an object to apply a method is similar to a procedure call in "traditional" programming languages. However, in object-orientation there is a view of autonomous objects which communicate with each other by exchanging messages. Objects react when they receive messages by applying methods on themselves. They also may deny the execution of a method, for example if the calling object is not allowed to execute the requested method.

In our example, the message and the method which should be applied once the message is received have the same name: We send "setValue with argument 1" to object i which applies "setValue(1)".

Definition 4.4.1 (Message) *A* **message** *is a request to an object to invoke one of its methods. A message therefore contains*

- *the* **name** *of the method and*
- *the* **arguments** *of the method.*

Consequently, invocation of a method is just a reaction caused by receipt of a message. This is only possible, if the method is actually known to the object.

Definition 4.4.2 (Method) *A* **method** *is associated with a class. An object invokes methods as a reaction to receipt of a message.*

4.5 Summary

To view a program as a collection of interacting objects is a fundamental principle in object-oriented programming. Objects in this collection react upon receipt of messages, changing their state according to invocation of methods which might cause other messages sent to other objects. This is illustrated in Figure 4.1.

In this figure, the program consists of only four objects. These objects send messages to each other, as indicated by the arrowed lines. Note that the third object sends itself a message.



Figure 4.1: A program consisting of four objects.

How does this view help us developing software? To answer this question let's recall how we have developed software for procedural programming languages. The first step was to divide the problem into smaller manageable pieces. Typically these pieces were oriented to the procedures which were taken place to solve the problem, rather than the involved data.

As an example consider your computer. Especially, how a character appears on the screen when you type a key. In a procedural environment you write down the several steps necessary to bring a character on the screen:

1. wait, until a key is pressed.
2. get key value
3. write key value at current cursor position
4. advance cursor position

You do not distinguish entities with well-defined properties and well-known behaviour. In an object-oriented environment you would distinguish the interacting objects *key* and *screen*. Once a key receive a message that it should change its state to be pressed, its corresponding object sends a message to the screen object. This message requests the screen object to display the associated key value.

4.6 Exercises

1. Class.
   (a) What distinguishes a class from an ADT?
   (b) Design a class for the ADT *Complex*. What representations do you choose for the ADT operations? Why?
2. Interacting objects. Have a look to your tasks of your day life. Choose one which does not involve too many steps (for example, watching TV, cooking a meal, etc.). Describe this task in procedural and object-oriented form. Try to begin viewing the world to consist of objects.
3. Object view. Regarding the last exercise, what problems do you encounter?
4. Messages.
   (a) Why do we talk about "messages" rather than "procedure calls"?
   (b) Name a few messages which make sense in the Internet environment. (You must therefore identify objects.)

(c) Why makes the term “message” more sense in the environment of the last exercise, than the term “procedure call”?